

Apacer

The Most **Reliable**
Storage For Industries

SV24P-25



SV24P-25

Overview

Apacer's SV24P-25 is a well-balanced solid-state disk (SSD) drive with standard form factor and great performance. Designed in SATA 6.0 Gb/s interface, the SSD is able to deliver exceptional read/write speed, making it the ideal companion for heavy-loading industrial or server operations.

SV24P-25 utilizes 3D NAND for higher capacity up to 1,920GB and provides more power efficiency than 2D NAND. Regarding reliability, SV24P-25 is implemented with LDPC (Low Density Parity Check) ECC engine to extend SSD endurance and increase data reliability. In addition, the drive comes with various implementations including powerful hardware ECC engine, power saving modes, wear leveling, flash block management, S.M.A.R.T. and TRIM.

In terms of security, Advanced Encryption Standard (AES) ensures data security and provides users with a peace of mind knowing their data is safeguarded. Furthermore, with End-to-End Data Protection, data integrity can be assured at multiple points in the path to enable reliable delivery of data transfers.




Feature

- Low-Density Parity-Check (LDPC) Code
- Global Wear Leveling
- Flash bad-block management
- Flash Translation Layer: Page Mapping
- S.M.A.R.T.
- ATA Secure Erase
- Device Sleep
- TRIM
- Hyper Cache Technology
- Over-Provisioning
- DataRAID™
- SMART Read Refresh™
- CorePower

Specifications

Model	SV24P-25
Interface	SATA 3.2 (6Gb/s)
Connector	(7+15) pin male
Form Factor	2.5"
NAND Flash Type	3D TLC
Capacity	120GB~1920GB
External DRAM	Yes
Sustained Read Performance (MB/sec)	Up to 560
Sustained Write Performance (MB/sec)	Up to 495
ECC Engine	Low-Density Parity-Check (LDPC) Code
IOPS (4K Random Write)	84K
Standard Operating Temperature (°C)	0 ~ + 70
Wide Temperature (°C)	-40 ~ + 85
Storage Temperature (°C)	-40 ~ + 100
Shock	Operation: 50(G)/11(ms) (compliant with MIL-STD-202G) Non-operation: 1,500(G)/0.5(ms) (compliant with MIL-STD-883K)
Vibration	Operation:7.69(Grms), 20~2000(Hz)/random (compliant with MIL-STD-810G) Non-operation:4.02(Grms), 15~2000(Hz)/random (compliant with MIL-STD-810G)
Operating Voltage	5.0 V ± 10%
Power Consumption	Active mode: 485mA / Idle mode: 65 mA
Dimension (L x W x H)	7mm:100.00 x 69.85 x 6.90mm
MTBF (hours)	>3,000,000

Mechanical Specification



Unit: mm

For more information,
contact your Apacer representative

Global Presence

Taiwan (Headquarters)
Apacer Technology Inc.
Tel: +886-2-2267-8000
Fax: +886-2-2267-2261

Europe
Apacer Technology B.V.
Tel: +31-40-267-0000
Fax: +31-40-290-0686

U.S.A.
Apacer Memory America, Inc.
Tel: +1-408-518-8699
Fax: 1-510-249-9551

Shanghai
Apacer Electronic(Shanghai)
Co., Ltd.
Tel: +86-21-6228-9939

Japan
Apacer Technology Corp.
Tel: +81-3-5419-2668
Fax: +81-3-5419-0018

India
Apacer Technologies Pvt. Ltd.
Tel: +91-80-41529061~3
Fax: +91-80-41700215